SHUR-LOK® FOR GRAIN TRAILERS SHUR-LOK® FOR GRAIN TRAILERS



AGRICULTURE DIVISION



IMPROVES YOUR SAFETY OF OPERATION

With proper tension, the tarp stays tight no matter your length of trailer. Standard crank is direct drive 1:1 and lets you roll the tarp standing safely on the ground. An upgrade to electric is available with our 4500 Series HD, plus more SMARTrailer[™] options like our ProTrap[®] and AutoTrap[™].

Standard easy-off tarp stops enable fast, easy tarp removal. Upgrading from the standard stretch cord return to cable return adds a non-stretch cable with heavy-duty internal tension spring-and-pulley. The patented design of our Wil-Slip[™] joint pull-out crank assembly allows the crank arm and U-joint to slide forward, bypassing hinges and clearing rear doors. This upgrade, ideal for open-top vans, Convertahoppers, belted floor trailers and "barn door" trailers, uses deeper caps that, if aluminum, are made of a heavier alloy. All require a cap depth of 26 inches.

Shur-Co[®] offers a wide variety of tarp fabric choices, like the new DiamondCore[™], a premium fabric that provides added substance, increased endurance and unparalleled abrasion resistance. Rock-solid quality backed by a 24-month warranty and currently only available in black.

Key Features: Aluminum Latchplate, Easy-Off Tarp Stops, Galvanized Bows/Brackets, Aluminum End Caps, 1" or 2" Ridge Strap w/Ratchet, Stretch Cord Return, Standard Crank Arm w/80" Extension, Pinless Crank Retainer w/7" Standoff, 18-Oz. Vinyl Tarp.

A005FL-0315



For more information, contact:

www.shurco.com


SHUR-LOK[®] BOX DETAILS | For Grain Trailers

MAKE	MODEL_		_ YEAR
Α	UPPER BOX LENGTH		
	A1	TAPERED	UPPER LENGTH
	A2	TAPERED	LOWER LENGTH
В	UPPER BOX WIDTH		
	Front C	Center	Rear
Ν	TOP RAIL WIDTH		
U	INSIDE BOX WIDTH		
Х	BOX HEIGHT		
CORNER CONFIGURATION			
SQUARE			RADIUS
с	OUTSIDE CORNER RADIUS For all radius fronts		
-			

E _____ FLAT ACROSS FRONT

- V _____ FLAT ACROSS DIAGONAL
- W _____ DIAGONAL DEPTH

To measure radius corners correctly, place a carpenter's square on the front radius of the trailer. Measure at the point where the radius starts to arch around the front of the trailer.



Shur-Lok[®] tarps are custom made to order and are nonreturnable. The correct measurements are essential for proper tarp fit. Please provide all requested information or your order may be delayed.

Please do not use universal box sizes; always use the actual physical measurements. Box size and finished tarp size are not the same.

