

# DRIVEMAXX™ ELECTRIC AUGER DRIVE



AGRICULTURE DIVISION



## SAFELY SWINGS YOUR AUGER INTO POSITION

A034FL-1118

The final component to Shur-Co's complete "system solution" for remote operation at harvest time. Quickly swings your auger hopper into position from the comfort of the cab. Comes with its own LiteALL™ work light kit and plug-and-play SMARTwire™ connections.

Independent 2-wheel dual-motor drive is powered by 220 lb.ft. of torque per motor. Direct-drive motors are designed with right-angle rear drives and no chains or chain tensioners. Sealed SMARTwire™ connections and receiver box, plus completely enclosed gear boxes, provide watertight reliability.

Included push-button LiteALL™ LED flood light can be upgraded to a SMART2™ or SMART3™ LiteALL™ for remote control. An open light channel lets you add a second LiteALL™ to illuminate auger discharge or for placement on the main auger tube to light the work area.

When combined with the rest of the SMARTrailer™ lineup, you can remotely operate all the things you do most frequently: rolling the tarp (4500 Series HD), swinging the auger hopper into position (DriveMaxx™ Auger Drive Kit), opening the traps (AutoTrap™ and ProTrap® Electric Hopper Openers) and adjusting grain flow from the truck into your auger (Electric Gate and Hoist) – even open your farm swing gates remotely.

**Key Features:** SMART Remote Compatibility, Independent 2-Wheel Dual-Motor Drive Kit, SMARTwire™ Connections, Sealed Receiver Box, Manual LiteALL™ LED Work Light Kit, SMART3™ Remote.



*For more information, contact:*

[www.shurco.com](http://www.shurco.com)

# DRIVEMAXX™ BOX DETAILS For Swing Augers

CORRECT PHYSICAL MEASUREMENTS ARE ESSENTIAL FOR PROPER TARP FIT. PROVIDE ALL REQUESTED INFORMATION OR YOUR ORDER MAY BE DELAYED. **DO NOT USE UNIVERSAL BOX SIZES. ALWAYS USE ACTUAL MEASUREMENTS. NOTE: AT THIS TIME, PRODUCT WILL NOT WORK WITH CONVEYOR BELT AUGERS.**

## CONTACT INFORMATION

NAME \_\_\_\_\_  
 ADDRESS \_\_\_\_\_  
 EMAIL \_\_\_\_\_  
 CITY \_\_\_\_\_ STATE \_\_\_\_\_ ZIP \_\_\_\_\_  
 PHONE \_\_\_\_\_ FAX \_\_\_\_\_  
 AUGER MAKE \_\_\_\_\_  
 MODEL \_\_\_\_\_ YEAR \_\_\_\_\_



Shur-Co®  
Dealer Locator



Drive Maxx™  
Landing Page

G13BD-1118

Call your local dealer for more information or use the QR code at the far left for our Dealer Locator. Or use the QR code for Shur-Co's DriveMaxx™ for more product details on our website.

## AUGER DIMENSIONS

A \_\_\_\_\_ TRANSITION BOX WIDTH (ACTUAL)

B TUBE DIAMETER

8"  10"  12"  13"  14"  16"

FLANGE  Yes  No

If yes, enter distance from edge of of flange to pre-existing mounting hole.

C \_\_\_\_\_

Current Remote:  SMART1+™  SMART2™  SMART3™

NOTE: If S1+, you MUST upgrade to:  SMART2™ OR  SMART3™

NOTE: If S2, remote is NOT included. If S3, remote comes standard.

**Non-Remote Controlled (Push-Button) LiteALL™ comes standard.**

To Upgrade:  SMART2™ LiteALL™ OR

SMART3™ LiteALL™

